



SPECIFICATIONS

- ① Housing Material: Polyamide 66(UL94V-0), Green
- ② Clamp: Nickel Plated Phosphor Bronze
- ③ Sprung: Zinc Plated Steel
- ④ lever: Polyamide 66(UL94V-0), Orange

Wier Range: 12~16 AWG
 Rated: 12 Amperes.AC250V
 Operation Temperature: -55°C~+115°C
 Insulation withstands volt: AC2000V min
 Insulation resistance: >1000MΩ or more at DC500V

Tolerance ± 0.50

POLE	2	3	4	5	6	7	8	9	10	11	12	
A	10.3	15.3	20.3	25.3	30.3	35.3	40.3	45.3	50.3	55.3	60.3	
B	5	10	15	20	25	30	35	40	45	50	55	
POLE	13	14	15	16	17	18	19	20	21	22	23	24
A	65.3	70.3	75.3	80.3	85.3	90.3	95.3	100.3	105.3	110.3	115.3	120.3
B	60	65	70	75	80	85	90	95	100	105	110	115

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 5.0mm TERMINAL BLOCK PLUGGABLE TYPE XXPIN SUITABLE FOR 12~16AWG NICKEL PLATED GREEN INSULATOR ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0936-XX4NE000R
DATE 制表日 2013/01/23	PAGE 張數 1 OF 1	REV. 版次 A	