



- Material**
- Item (a) Clamp: Brass(CuZn) Ni plated
 - Item (b) Terminal screw: Steel Zinc plating "-" slot type
 - ▲ Item (c) Female contact: PhBz ,Bright Tin plated over Nickel plated
 - Item (d) Terminal Cover: Thermoplastic (UL94V-0)
 - Item (e) Terminal housing: Thermoplastic (UL94V-0)

- Electrical cULus**
- Voltage rating: 300VAC
 - Current rating: 20A
 - Wire range:
 - Solid wire(AWG): 12-24
 - Stranded wire(AWG): 12-24
 - Torque: 5Lb-In
 - Screw: M3
 - Wire strip length: 7-8mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval: US
 - Critical dimension: ▽

N = Number of poles
 Dim A=(N-1)X7.62+5.62
 Dim B=(N-1)x7.62

Poles	Tolerance
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.30

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 HELEN</p>	<p>SCALE 比例 參考</p>	<p>TOLERANCE 容許公差 X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*</p>	<p>PART NAME 品名 7.62mm TERMINAL BLOCK XXPIN WIRE CAGE TYPE SUITABLE FOR 12-24AWG TIN PLATED GREEN INSULATOR SCREWS ZINC PLATING W/O EARS(SCREWS HOLE) ROHS</p>
<p>DWG. 製圖 ABBY</p>	<p>UNIT 單位 MM</p>	<p>SIZE. 紙張尺寸 A4</p>	<p>PART NO. 料號 C0955-XX5TGN00R</p>
<p>DATE 制表日 2020/06/17</p>	<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>	