



LTR	Part Name	Material	Description	QTY
1	Housing	Nylon	260°C for 10 Seconds . Initial : 1000M Ohms Min. After Test : 500M Ohms Min.	1
2	Contact	Brass	Current Rating : 0.75A Initial : 20m Ohms Max. After Test : 40m Ohms Max.	XX

Temperature Rating : -40°C ~ +125°C .  
 Dielectric Withstanding Voltage : 500V AC/Min

C=2.2mm D=4.6mm E=1.8mm

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日	SCALE 比例 UNIT 單位 PAGE 張數	TOLERANCE 容許公差 .0 ± 0.3 .00 ± 0.2 ANG. ± 1° SIZE 紙張尺寸 A4 REV. 版本 A	PART NAME 品名 0.8X1.2mm PIN HEADER DUAL ROW SMT 2X??P H=1.38mm GOLD FLASH(C=2.2 D=4.6 E=1.8mm) W/O LOCATING PEG ROHS PART NO. 料號 C1808-XXBDGBAXR
Helen	M M	1 OF 1	
2012/10/8			