



CIRCUIT	DIM "A"	DIM "B"
2	2 (0.079)	4 (0.157)
3	4 (0.157)	6 (0.236)
4	6 (0.236)	8 (0.315)
5	8 (0.315)	10 (0.393)
6	10 (0.393)	12 (0.472)
7	12 (0.472)	14 (0.551)
8	14 (0.551)	16 (0.630)
9	16 (0.630)	18 (0.709)
10	18 (0.709)	20 (0.787)
11	20 (0.787)	22 (0.866)

FEATURES

Double tuning fork type contact guarantees high reliability.
2.0MM pitch Low-Profile mini type Match to 0.50mm sq. posts.

MATERIAL

.Insulator30% Glass Filled P.B.T.(UL 94v-0)
.ContactGold Plated
.Terminal5191 Phosphor Bronze

SPECIFICATIONS

.Current Rating: 2 amperes MAX
.Contact Resistance: 30m ΩMAX
.Insulation Resistance: 1000 megohms MAX
.Dielectric Withstanding Voltage: AC 550 volts RMS at sea level

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 HELEN	 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 2.0mm MULTI JUMPER XXP H:4.3mm PARALLEL TYPE BLACK COLOR ROHS
DWG. 製圖 ABBY		DATE 制表日 2012/09/11	SIZE. 紙張尺寸 A4 REV. 版次 B