



**SPECIFICATIONS**  
 Rated Current: 3.0AMP  
 Contact Resistance: 20mΩ Max  
 Withstand Voltage: 1000V AC/DC  
 Insulation Resistance: 1000MΩ Min  
 Operation Temperature: -40°C to +105°C

Contact Material: Brass  
 Contact Plating: Au or Sn Over Ni  
 Insulator Material: Polyester (UL94V-0)  
 Standard: PBT  
 Max. Processing Temp: 180°C for 30-60 seconds  
 (200°C for 10 seconds)

PART NO
08
10
14
16
20
24
26
30
34
40
50
60
64

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2014/08/06	Betty	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	PART NAME 品名 BOX HEADER IDC TYPE 2.54mm X 2.54mm 2XXXP WITHOUT S/R WITHOUT EAR SELECTIVE GOLD PLATING GREY COLOR ROHS PART NO. 料號 C3501-XXNNSG00R