



Material:

Housing: 30% Glass Filled PBT UL 94V-0.
 Contacts: Brass.

Electrical Characteristics:

Current Rating: 1 AMP.
 Dielectric Withstanding Voltage: AC 500V For 1 Minute
 Insulator Resistance: 1000MΩ min. at DC 500V.
 Contact Resistance: 20mΩ max. at DC 100mA.
 Operating Temperature: -55°C ~ +105°C .

***RoHS Compliant**

Position	Dimension		
	A	B	C
20	20.95	11.43	18.75
26	24.76	15.24	22.56
32	28.57	19.05	26.37
34	29.84	20.32	27.64
40	33.65	24.13	31.45
50	40.00	30.48	37.80
52	41.27	31.75	39.07
60	46.35	36.83	44.15
68	51.43	41.91	49.23
80	59.05	49.53	56.85
100	71.75	62.23	69.55

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	TOLERANCE 容許公差 x = ±0.5 .x = ±0.25 .xx = ±0.15	PART NAME 品名 BOX HEADER H.D 1.27mm X 2.54mm XXP 180° BLACK COLOR 4 ROWS ROHS LOW-LEAD
DWG. 製圖	BETTY		SCALE 比例 參考
DATE 制表日	2009/03/13	UNIT 單位 M M	REV. 版次 A
		PAGE 張數 1 OF 1	