



SPECIFICATIONS

Current Rating : 3AMP
Operation Temperature: -40° C to +105° C
Contact Resistance : 20m Ω Max.
Insulation Resistance: 1000M Ω Min.
Withstanding Voltage : AC 1000V
Insulator Material : Polyester (UL94V-0)
Standard: PA46
Contact Material : Brass
Contact plating : Au or Sn over 50u" Ni

C **3506** — **08** **D** **E** **G** **B** **P** **N** **R**
 1 2 3 4 5 6 7 8 9 10

- | | | | |
|---|---------------------------------------|---|---|
| 1. PRODUCTS: C: Connector | 5. INSULATOR MATERIAL: E: Nylon 46 | 7. INSULATOR COLOR: B: Black | 8. PACKING STYLE: P: PAD+Tube Packing Q: PAD+Reel Packing |
| 2. SERIES NO.: 3506 | 6. CONTACT PLATING: G: Gold Flash | 9. BODY OPTION: N: W/O Locating Peg 10. R: ROHS | |
| 3. CONTACT NO.: 08, 10, 12, 14, 16 20, 22, 26, 30, 34 40, 44, 50, 60, 68 80 | 4. CONTACT TYPE: D: S.M.T. | | |

| | | |
|--------------------------|--|---|
| RoHS Compliant | HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| | APPD. 核准 DWG. 製圖 Hedy DATE 制表日 2013/12/19 | TOLERANCE 容許公差 X: ±0.30 X*: ±1° XX: ±0.20 XX*: ±0.05° XXX: ±0.15 XXX*: ±0.05° UNIT 單位 M M PAGE 張數 1 / 1 SCALE 比例 參考 SIZE 紙張尺寸 A 4 REV. 版次 A |