



### SPECIFICATIONS

Current Rating : 1AMP  
 Operation Temperature: -40° C to +105° C  
 Contact Resistance : 20mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage : AC 500V  
 Insulator Material : Polyester (UL94V-0)  
 Standard: PA6T  
 Contact Material : Brass  
 Contact plating : Au or Sn over 50u" Ni

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		TOLERANCE 容許公差 X: ±0.30 X*: ±1* XX: ±0.20 XX*: ±0.06* XXX: ±0.15 XXX*: ±0.05*	PART NAME 品名 1.27mm X 1.27mm BOX HEADER H=4.9mm XXP RIGHT ANGLE TYPE GOLD FLASH PLATING BLACK COLOR PA6T UL94-V0 WITHOUT LOCATING PEG TRAY PACKING ROHS
DWG. 製圖 Hedy	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A 4
DATE 制表日 2015/11/26	PAGE 張數 1 / 1	REV. 版次 A	PART NO. 料號 C3506-XXRNGB0NR