



SPECIFICATIONS

Current Rating : 3AMP
 Operation Temperature: -40°C to $+105^{\circ}\text{C}$
 Contact Resistance : $20\text{m}\Omega$ Max.
 Insulation Resistance: $1000\text{M}\Omega$ Min.
 Withstanding Voltage : AC 1000V
 Insulator Material : Polyester (UL94V-0)
 Standard: PA46
 Contact Material : Brass
 Contact plating : Au or Sn over $50\mu\text{Ni}$

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE X: $\pm 0,30$ X.X: $\pm 0,20$ X*: $\pm 1^*$ X.XX: $\pm 0,15$ X.X*: $\pm 0,05^*$ X.XXX: $\pm 0,05$	PART NAME 品名 1.27mm X 1.27mm BOX HEADER H=4.9mm XXP STRAIGHT TYPE BLACK INSULATOR NYLON 46 UL94-V0 WITHOUT LOCATING PEG ROHS
DWG. 製圖 Betty		SIZE. 紙張尺寸 A 4	PART NO. 料號 C3506-XXSEXBXNR
DATE 制表日 2012/10/25	REV. 版次 A		