



NOTE:

1. Insulator Material : LCP
2. Terminal Material : Brass
3. Plating : Tin
4. Operating temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
5. Rated voltage: 250V, AC, DC
6. Contact resistance : $\leq 0.04\Omega$
7. Insulation resistance: $\geq 800\text{m}\Omega$
8. Withstand voltage: 200V, AC/minute

DIM	TOL	DIM	TOL
X.	± 0.25	X.	/
X.X	± 0.20	X.X	$\pm 2^{\circ}$
X.XX	± 0.15	X.XX	$\pm 1^{\circ}$
X.XXX	± 0.05	X.XXX	

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD.
核准
Betty
DATE 制表日
2019/08/28

SCALE
比例 參考
UNIT
單位 MM
PAGE
張數 1 OF 1

PART NAME 品名
2.0mm & 2.5mm LED CONNECTOR 3PIN
FEMALE SMT 90° TYPE WITH LOCATING PEG
MATERIAL: BRASS TIN PLATING REEL PACKING
BEIGE COLOR (MATERIAL: LCP) ROHS
PART NO.
料號 C3805-03BYTRC0R