



- SPEC :
- Housing: High-Temp Plastic,UL94-V  
Color:Nature (Ivory)(LCP)
  - Locker: High-Temp Plastic,UL94-V  
Color:Black(LCP)
  - Contact: Phosphor Bronze(C5191)  
Initial: 30m Ohms Max.  
Voltage Rating: 50V AC,DC
  - Solder Tab: BRASS(C2680)
  - Temperature Rating : -25°C ~ +85°C
  - Dielectric Withstanding Voltage : 500V AC/Min
  - Current Rating : 0.4A DC
  - Insulation Resistance: 50M Ohms Min
  - Contact Resistance: 100m Ohms Max

(N)	N*0.5+2.0	(N-1)*0.5	N*0.5+0.57	N*0.5+1.39	N*0.5+1.1	N*0.5+1.9	N*0.5+0.5
50	27.00	24.50	25.57	26.39	26.10	26.90	25.50
40	22.00	19.50	20.57	21.39	21.10	21.90	20.50
34	19.00	16.50	17.57	18.39	18.10	18.90	17.50
32	18.00	15.50	16.57	17.39	17.10	17.90	16.50
30	17.00	14.50	15.57	16.39	16.10	16.90	15.50
26	15.00	12.50	13.57	14.39	14.10	14.90	13.50
24	14.00	11.50	12.57	13.39	13.10	13.90	12.50
23	13.50	11.00	12.07	12.89	12.60	13.40	12.00
22	13.00	10.50	11.57	12.39	12.10	12.90	11.50
20	12.00	9.50	10.57	11.39	11.10	11.90	10.50
16	10.00	7.50	8.57	9.39	9.10	9.90	8.50
14	9.00	6.50	7.57	8.39	8.10	8.90	7.50
12	8.00	5.50	6.57	7.39	7.10	7.90	6.50
11	7.50	5.00	6.07	6.89	6.60	7.40	6.00
10	7.00	4.50	5.57	6.39	6.10	6.90	5.50
8	6.00	3.50	4.57	5.39	5.10	5.90	4.50
7	5.50	3.00	4.07	4.89	4.60	5.40	4.00
6	5.00	2.50	3.57	4.39	4.10	4.90	3.50
4	4.00	1.50	2.57	3.39	3.10	3.90	2.50
Number of Pin	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	DIM G



RoHS Compliant

**HSM** 玄茂科技股份有限公司

**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	Betty		TOLERANCE	PART NAME 品名
DWG. 製圖	Lena		.X ±0.30 .XX ±0.20 .XXX ±0.10 ANGULAR ±3'	FPC/FFC ZIF 0.5mm SMT TYPE XXP DUAL CONTACT REEL PACKING GOLD PLATING IVORY COLOR ROHS
DATE 制表日	2020/6/11	UNIT 單位	MM	PART NO.
PAGE 張數	1 OF 1	REV. 版本	A	料號 C3947-XXDGR100R