



No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
-	-	-	12	13.97	15.24	22	26.67	27.94
03	2.54	3.81	13	15.24	16.51	23	27.94	29.21
04	3.81	5.08	14	16.51	17.78	24	29.21	30.48
05	5.08	6.35	15	17.78	19.05	25	30.48	31.75
06	6.35	7.62	16	19.05	20.32	26	31.75	33.02
07	7.62	8.89	17	20.32	21.59	27	33.02	34.29
08	8.89	10.16	18	21.59	22.86	28	34.29	35.56
09	10.16	11.43	19	22.86	24.13	29	35.56	36.83
10	11.43	12.70	20	24.13	25.40	30	36.83	38.10
11	12.70	13.97	21	25.40	26.67	31	38.10	39.37

No. of Pins/Row	Dimension Information		No. of Pins/Row	Dimension Information	
32	39.37	40.64	42	52.07	53.34
33	40.64	41.91	43	53.34	54.61
34	41.91	43.18	44	54.61	55.88
35	43.18	44.45	45	55.88	57.15
36	44.45	45.72	46	57.15	58.42
37	45.72	46.99	47	58.42	59.69
38	46.99	48.26	48	59.69	60.96
39	48.26	49.53	49	60.96	62.23
40	49.53	50.80	50	62.23	63.50
41	50.80	52.07			

SPECIFICATIONS

Current Rating: 1 Amp.
 Insulator Resistance: 5000 Megohms. Min.
 Dielectric Withstanding: AC 500V.
 Operating Temperature: -40°C ~ +105°C.
 Max. Processing Temp: 230°C For 30~60 Seconds
 (260°C For 10 Seconds)
 Contact: Phosphor Bronze.
 Housing: Nylon 6T(UL94V-0)

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 DATE 制表日 Betty 2012/08/06	TOLERANCE 容許公差 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	PART NAME 品名 1.27 X 2.54mm FEMALE HEADER DUAL ROW H:4.6mm 2X??P STRAIGHT TYPE GOLD PLATING ROHS PART NO. 料號 C4827-XXBSGH00R	TOLERANCE 容許公差 .00 ± 0.2 ANG. ± SIZE 紙張尺寸 A4 REV. 版本 C