



## NOTE

### A. Material:

1. Housing : Nylon-9T Halogen Free, UL94V-0, Black

2. Contact : Copper Alloy

B. Plating: Gold plating

C. Temperature: -55 to 125

### D. Electrical:

1. Voltage : 50V.

2. Current : 0.5A.

3. Contact Resistance :  $40m \Omega$  max.

4. Dielectric Withstanding Voltage :  
500V AC / 1 min.

5. Insulation Resistance :  $100M \Omega$  min.

Available Pins : 10~100 Contacts 

RoHS Compliant		<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 参考	TOLERANCE 容許公差 .X $\pm 0.25$ .XX $\pm 0.10$ .XXX $\pm 0.05$	PART NAME 品名 0.8mm BOARD TO BOARD MALE ASSEMBLY STRAIGHT TYPE 2XXXP 氏, H=3.55mm (ASSEMBLY H=4.6mm or 6.0mm or 6.5mm or 7.0mm) GOLD FLASH PLATING WITH LOCATING PEG BLACK COLOR WITH PAD ROHS
DWG. 製圖 ABBY	UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C6008-XXMNGBX0R
DATE 制表日 2018/04/19	PAGE 張數 1 OF 1	REV. 版次 A	