



SPECIFICATION

MATERIAL
 Insulator: Thermal Plastic UL94V-0
 Contacts: Copper Alloy
 Mount Ear: Copper Alloy
CONTACT PLATING
 Underplate: 50u"~100u" Nickel
 Contact Area: 1u"~30u" Selective Gold
 Solder Tails Area: 100u"~200u" Tin/Lead Free(Brighten Tin/Matte Tin)

OPTION:
 C7753-50AAYXWXR :W/LOCKING (TYPE 2 ONLY)
 C7753-50AANXWXR :W/O LOCKING

POWER	5.00mm	1,13,38,50
GENERAL	4.25mm	all other pins
DETECT	3.50mm	25,26
Pin type	Interface Dim. L	Pin No.

RECOMMENDED P.C.B LAYOUT
 TOLERANCES: ±0.05mm

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	BETTY	SCALE 比例	TOLERANCE 容許公差
DWG. 製圖	KAREN		
DATE 制表日	2012/08/28	UNIT 單位	SIZE 紙張尺寸
		PAGE 張數	REV. 版次

PART NAME 品名	CF CARD SOCKET SMT TYPE2 50PIN MALE STAND OFF:0mm ROHS LOW-LEAD
PART NO. 料號	C7753-50AAXXWXR