



Specifications rating :

100V AC 1A MAX
 contact resistance :
 pins-30mΩ MAX; shell-50mΩ MAX
 insulation resistance :
 MIN 100 MEGΩ @500V DC
 voltage withstand :
 250V AC R.M.S. for 1 minute

No.	Description	Material	Treat	Q'ty
5	Contact Terminals	Brass	Nickel Ptd.	13
4	13P Housing	ABS		1
3	Shield Cover B	Steel	Nickel Ptd.	1
2	Shield Cover A	Steel	Nickel Ptd.	1
1	Shell Cover	EVA + LLDPE		1

RoHS Compliant
APPD. 核准 HELEN
DWG. 製圖 ABBY
DATE 制表日 2015/11/16

SCALE 比例 參考	TOLERANCE 容許公差 .0 ±0.25 .00 ±0.10 .000 ±
UNIT 單位 MM	SIZE. 紙張尺寸 A 4
PAGE 張數 1 OF 1	REV. 版次 A

HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
PART NAME 品名 DIN PLUG ASSEMBLY TYPE 13P MALE NICKEL PLATING ROHS	
PART NO. 料號	C8000-13MBNB00R