



SPECIFICATIONS:

1. CONTACT RESISTANCE : 20m OHM MAX.
2. INSULATION RESISTANCE : 300M OHM MIN. AT DC 500V.
3. VOLTAGE WITHSTANDING : AC 1000V FOR ONE MINUTE.
4. INSERTION FORCE : 4.0KG MAX.
5. WITHDRAWAL FORCE : 1 - 3.5KG.

5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	4-8	BRASS 0.7t	TIN	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	TIN	
2.	INSULATOR	1	P.B.T.		UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

ARRANGEMENT OF CONTACTS					
NO OF CONTACTS	4	5	6	7	8

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 Betty	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 DIN SOCKET METAL COVER TYPE SOLDER TYPE XXP TIN PLATING BLACK COLOR ROHS PART NO. 料號 C8015-XXATB000R
-------------------	--	---	--