



Specifications rating :  
 100V AC 1A MAX  
 contact resistance :  
 pins-30mΩ MAX; shell-50mΩ MAX  
 insulation resistance :  
 MIN 100 MEGΩ @500V DC  
 voltage withstand :  
 250V AC R.M.S. for 1 minute

section A-A



8	Terminals	Brass	Silver Ptd.	4
7	Housing	PA66		1
6	Strain Boot	PVC		1
5	Set Screw	Steel	Nickel Ptd.	1
4	Spring	Steel	Nickel Ptd.	1
3	"T" Cable Holder	Steel	Nickel Ptd.	1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 HELEN		TOLERANCE 容許公差 .0 ±0.25 .00 ±0.10 ANG±	PART NAME 品名 DIN CABLE JACK SCREW LOCK 4P FEMALE NICKEL SHELL SILVER PLATING BALCK INSULATOR(NYLON 66) ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A 4
DATE 制表日 2017/02/23	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8020-04FVB000L