



A-A SECTION



Specifications rating :

- 100V AC 1A MAX**
- contact resistance :**
pins-30mΩ MAX; shell-50mΩ MAX
- insulation resistance :**
MIN 100 MEGΩ @500V DC
- voltage withstand :**
250V AC R.M.S. for 1 minute

8	Contact Terminals	Brass	Silver Ptd.	4
7	4P Housing	PA66		1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Setscrew	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strain Boot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE 容許公差 .0 ±0.25 .00 ±0.10 .000 ±	PART NAME 品名 DIN CABLE JACK SCREW LOCK 4P MALE NICKEL SHELL SILVER PLATING BALCK INSULATOR(PA66) ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	SIZE. 紙張尺寸 A 4
DATE 制表日 2016/08/03	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8020-04MVB000L