



SPECIFICATIONS	
Dielectric strength	1,000V AC/1 Minute
Contact resistance	20mΩ Max.
Insulation resistance	100MΩ Min. at 500V DC
Rating	100V AC 2A

ARRANGEMENT OF CONTACTS									
PARTS	3P	4P	5P		6P	7P	8P		
ANGLE	180°	216°	180°	240°	360°	240°	270°	270°	262°
POSITION OF VIEWS									

4	HEX. NUT	1	DIECAST ALLOY	NICKEL	30-50U"
3	METAL BODY	1	DIECAST ALLOY	NICKEL	30-50U"
2	CONTACT TERMINAL	3-8	BSR-H (0.6t) [C2680R]	SILVER PLATED	30-50U"
1	PLASTIC CORE	1	NYLON [101]		UL94V2
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准 DWG. 製圖 DATE 制表日 2018/01/04	Betty	 SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± .00 ± ANG ± SIZE 紙張尺寸 A 4 REV. 版次 C	PART NAME 品名 DIN SOCKET PANEL MOUNT SCREW LOCKING TYPE XXP FEMALE NICKEL SHELL SILVER PLATING BALCK INSULATOR(PA66) ROHS PART NO. 料號 C8021-XXFVBX00R
---	-------	--	---	--