



NO.	NAME	Q'TY	MATERIAL	FINISH
8				
7	SHELL	1	Iron0.4	D. Cu/Sn
6	RING	1	H62 Brass Y=0.38mm	D. Cu/Sn
5	TERMINAL	1	H62 Brass Y=0.35mm	D. Cu/Sn
4	RIGHT PIN(SHORT)	1	H62 Brass Y=0.28mm	D. Cu/Sn
3	LEFT PIN(SHORT)	1	H62 Brass Y=0.28mm	D. Cu/Sn
2	COVER	1	PBT	Black
1	BASE	1	PBT	Black

NOTE :

1. RATING : DC30V 0.3A
2. CONTACT RESISTANCE : $\leq 0.03\Omega$
3. INSULATOR RESISTANCE : $\geq 100M\Omega$
4. WITHSTAND VOLTAGE : AC250V (50Hz) 1min
5. WITHDRAW FORCE : 5~30N
6. LIFE TEST : 5,000 cycles

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准</p>		<p>TOLERANCE 容許公差</p> <p>.0 ± 0.30</p> <p>.00 ± 0.20</p> <p>ANG. ± 3°</p>	<p>PART NAME 品名</p> <p>MINI DIN JACK 3P WITH FULLY SHIELDED WITH BOARDLOCK FOOT MATERIAL : PBT BLACK INSULATOR ROHS</p>
<p>DWG. 製圖</p> <p>Betty</p>	<p>SCALE 比例</p> <p>參考</p>	<p>UNIT 單位</p> <p>MM</p>	<p>PART NO.</p> <p>料號 C8023-03FAFTB0R</p>
<p>DATE 制表日</p> <p>2016/09/23</p>	<p>PAGE 張數</p> <p>1 OF 1</p>	<p>REV. 版次</p> <p>A</p>	