



RATING: DC20V 7.5A  
 WITHSTAND VOLTAGE: AC500V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30\text{m}\Omega$  max  
 INSULATION RESISTANCE:  $\geq 100\text{M}\Omega$  min  
 WITHDRAW FORCE: 10-50N  
 LIFE TEST: 1,000 cycles

6				
5	SHELL	BRASS	1	Ni-PLATED
4	COVER	PBT	1	
3	SPRING	BRASS	1	Ni-PLATED
2	TERMINAL	BRASS	4	Ag-PLATED
1	HOUSING	PBT	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty	SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3° SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 MINI DIN JACK 4P WITH FULLY SHIELDED WITH KINK FOOT MATERIAL : PBT BLACK INSULATOR ROHS PART NO. 料號 C8023-04FBFVB0R
DATE 制表日 2017/08/08			