



**SPECIFICATIONS**

Contact resistance	30mΩ Max.
Dielectric strength	250V AC/1 Minute
Insulation resistance	50MΩ Min. at 250V DC
Rating	100V AC 1A Max.; 12V DC 2A Max.
Insertion force	4.5Kg Max.
Withdrawal force	0.9Kg ~ 3Kg

3	HEX. NUT	1	BRASS	NICKEL	30-50u"
3	EARTH TERMINAL	1	BSR-H (0.3t) [C2680R]	NICKEL	30-50u"
2	CONTACT TERMINAL	8	BSR-H (0.2t) [C1519R-H]	SILVER PLATED	30-50u"
1	PLASTIC BODY	1	PBT [D202G15]		UL94HB
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	MINI DIN JACK SQUARE HOLE TYPE XXPIN VERTICAL TYPE WITH NUT WITHOUT LOCK PIN: SILVER PLATED ROHS
DATE 制表日	2016/11/18	UNIT 單位 M M	PART NO.
		PAGE 張數 1 OF 1	料號 C8096-XXPVBYN0R
		REV. 版次 A	