


T:1.6 Dimensions of PC board holes
Tolerance : ±0.05(Printed-top view)



SCHEMATIC DIAGRAM

Specification:
Rated Voltage / Rated Current : AC 100V 1A or DC 12V 2A MAX
Operating Temp: -40°C~+85°C
Insulation Resistance:50MΩ min
Dielectric Withstanding Voltage: 250V AC For 1min
Contact Resistance:30mΩ

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

| | | | |
|------------------------|-------------------|--|---|
| APPD. 核准 | | TOLERANCE X.X ±0.38 X.X' ±3 X.XX ±0.30 X.XX' ±1 X.XXX ±0.25 | PART NAME 品名 MINI DIN JACK WITH SCREW 6P WITH FULLY SHIELDED HOOK PIN WITH BOARDLOCK BLACK INSULATOR SELECTIVE GOLD PLATING ROHS |
| DWG. 製圖 | Betty | SCALE 比例 參考 | PART NO. 料號 C8098-06YHSB00R |
| DATE 制表日 2018/03/06 | UNIT 單位 M M | SIZE 紙張尺寸 A 4 | |
| | PAGE 張數 1 OF 1 | REV. 版次 A | |

| | | | | | |
|-----|--------------|-----|----------|---------|---------|
| 4 | COAT | 1 | C2680 | Cu/Sn | PLATED |
| 3 | CONTACT FOOT | 6 | C5191 | Ag | PLATED |
| 2 | COVER | 1 | C2680 | Cu/Sn | PLATED |
| 1 | HOUSING | 1 | PBT 4815 | UL-94V0 | (BLACK) |
| LTR | PART NAME | QTY | MATERIAL | REMARK | |