


Specification:
 Contact Resistance: 30m Ohm Max. At AC 100mA Max.1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V,2A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0 Kg.



| NO. | NAME | MATERIAL | FINISH | Q'TY |
|-----|--------------|-------------------|-------------|------|
| 1 | BARREL | BRASS T:0.4 | GOLD PLATED | 1 |
| 2 | TERMINAL | BRASS T:0.5 | TIN PLATED | 1 |
| 3 | SPRING TERM. | PHOS.BRZONE T:0.3 | TIN PLATED | 1 |
| 4 | HOUSING | PBT G.F. | WHITE | 1 |

RoHS Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准
 DWG. 製圖 *Helen*
 DATE 制表日
 2015/11/19

SCALE 比例 參考
 UNIT 單位 MM
 PAGE 張數 1 OF 1

TOLERANCE 容許公差
 0 ±0.38
 .00 ±0.25
 ANG. ±3°
 SIZE 紙張尺寸 A4
 REV. 版本 A

PART NAME 品名
 RCA JACK RIGHT ANGLE 3P W/3 POSTS WHITE
 INSULATOR SHELL:BRASS / GOLD PLATING
 TERMINAL:TIN PLATING ROHS

PART NO.
 料號 C8105-03ASW000R