



Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max. 1KHz.
 Insulation Resistance: 100M Ohm Min. At 500V DC.
 Rated Voltage And Current: DC 12V, 2A Max ; AC 100V, 1A Max.
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.
 Durability (Life Test): 4000 Cycles.
 Insertion Force: 0.3~3.0 Kg.
 Extraction Force: 0.3~3.0 Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	C.R.S T:0.3	GOLD-PLATED	1
2	TERMINAL	BRASS T:0.25	GOLD-PLATED	1
3	BRACKET	C.R.S T:0.4	GOLD-PLATED	1
4	INSULATOR	PBT G.F.	WHITE	1
5	RING	PBT G.F.	RED	1

APPD. 核准 DWG. 製圖 DATE 制表日 2016/7/18	SCALE 比例 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 X. ±0.38 .X ±0.25 .XX ±0.13 SIZE 紙張尺寸 A 4 REV. 版本 A	PART NAME 品名 RCA JACK 2 CONTACTS RED INSULATOR GOLD FLASH PLATING ROHS
			PART NO. 料號 C8106-02GR0000R

RoHS Compliant **HSM** 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.