



Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max 1KHz  
 Insulation Resistance: 100M Ohm Min. At 500V DC.  
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max  
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute  
 Durability (Life Test): 4000 Cycles  
 Insertion Force: 0.3~3.0 Kg  
 Extraction Force: 0.3~3.0Kg

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.4	NICKEL PLATED	3
2	JACK HOUSING	PBT G.F.	RED/WHITE/YELLOW	3
3	ASSEM. HOUSING	ABS	BLACK	1
4	CONTACT TERM.	BRASS T:0.5	TIN PLATED	3

<b>RoHS Compliant</b>	<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
	APPD. 核准 HELEN DWG. 製圖 ABBY DATE 制表日 2013/07/05	 TOLERANCE 容許公差 X ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1