



RATING: DC30V 0.3A
 WITHSTAND VOLTAGE: AC500V(50Hz)/min
 CONTACT RESISTANCE: $\leq 30m\Omega$
 INSULATION RESISTANCE: $\geq 100M\Omega$
 WITHDRAW FORCE: 3-25N
 LIFE TEST: 5,000 cycles

2	TERMINAL	BRASS	4	Ag-PLATED
1	HOUSING	PBT	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATING

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE 容許公差 .0 ±0.1 .00 ±0.05 ANG. ±	PART NAME 品名 3.5Φ EARPHONE JACK 5P WITH TWO PLASTIC POSTS WITHOUT BARRICADE SILVER PLATING BLACK INSULATOR
DWG. 製圖 ABBY	SCALE 比例 參考	SIZE. 紙張尺寸 A4	PART NO. 料號 C8115-05CNVB00R
DATE 制表日 2013/11/06	UNIT 單位 M M	REV. 版次 B	
	PAGE 張數 1 OF 1		