



Specification:  
 Contact Resistance: 30m Ohm. Max. At AC 100mA Max. 1KHz.  
 Insulation Resistance: 100M Ohm Min. At 500V DC.  
 Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.  
 Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.  
 Durability (Life Test): 4000 Cycles.  
 Insertion Force: 0.3~3.0 Kg.  
 Extraction Force: 0.3~3.0 Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.4	NICKEL PLATED	2
2	INSERT RING	PBT G.F.	WHITE,RED	4
3	COVER	ABS	BLACK	2
4	HOUSING	ABS	RED	1
5	TERM.	BRASS T:0.5	TIN PLATED	2
6	TERM.	BRASS T:0.5	TIN PLATED	2

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05	RCA JACK 4 PORT RIGHT ANGLE TYPE TIN PLATED RED RED/WHITE WHITE (TOP ROW:WHITE/WHITE COLOR BOTTOM ROW:RED/RED COLOR) ROHS
DATE 制表日	2023/08/22	UNIT 單位	PART NO.
		M M	料號 C8120-04RT0000R
		PAGE 張數	
		1 OF 1	
		REV. 版次	
		C	