



Pin Hole Layout
(Jack Bottom View)

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Current Rating : Max 5.0A , 24V DC
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

6.	Cover	PA9T	1	Black Color
5.	Housing	PA9T	1	Black Color
4.	Pin(2.5φ)	Copper	1	Nickel Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Sleeve Spring	0.25T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2016/07/07	PAGE 張數 1 OF 1	REV. 版次 B
PART NAME 品名 DC POWER JACK PIN :2.5mm NORMAL CLOSE TYPE FLAT TYPE SILVER PLATED BLACK COLOR WITHOUT LOCATING PEG ROHS		PART NO. 料號 C8125-DCVBN000R