



T:1.6 Dimensions of PC board holes
Tolerance : ±0.05(Printed-top view)

5	HOUSING	1	PA9T	UL-94V0(BLACK)
4	PIN	1	H59(COPPER ALLOY)	Cu/Sn PLATED
3	TERMINAL 3#	1	C2680 t=0.25	Ag PLATED
2	TERMINAL 2#	1	C5191 t=0.30	Ag PLATED
1	TERMINAL 1#	1	C2680 t=0.30	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	DC POWER JACK SMT TYPE PIN∅1.3mm NORMAL CLOSE TYPE WITH LOCATING PEG SILVER PLATING BLACK INSULATOR REEL PACKING ROHS
DATE 制表日	2015/06/24	UNIT 單位 M M	PART NO.
		PAGE 張數 1 OF 1	料號 C8142-ACVBYR00R
		REV. 版次 A	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.2