



Specification:
 Current Rating: 5A
 Voltage Rating: 750V max
 Operating Temp: -30°C~+60°C
 Insulation Resistance: ≤100MΩ
 Dielectric Withstanding Voltage: 2000V rms
 Contact Resistance: ≤20mΩ

7	FERRULE	BRASS
6	CRIMPING PATCH	BRASS
5	DIELECTRIC	ABS
4	BODY	BRASS
3	PLASTIC HANDLE	PE
2	DIELECTRIC	POM
1	FRONT POINT	BRASS
ITEM	DESIGNATION	MATERIAL

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE 容許公差 0 - 10 ±0.05 10 - 99 ±0.5 100 - 999 ±10.0 1000 - 9999 ±100.0 10000 - 99999 ±1000.00	PART NAME 品名 Φ3.5mm PHONE PLUG 4POLE PLASTIC OCTAGON TYPE(PE) NICKEL PLATING BLACK COLOR ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2014/03/25	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8150-04MBENB0R