



NOTES:

1.Specification:

- 1>.Operation force: 1000gf Max.
- 2>.Operation Temperature: -30 °C to +85°C.
- 3>.Storage Temperature: -40 °C to +85°C.
- 4>.Mechanical Life: 1000 cycles operations.
- 5>.Resistance to Soldering: 260 ±5°C for 3-5 Seconds.

2.PLATING:

- 1>.GOLD flash 1u" (min) SOLDERTAIL, 3u" GOLD PLATING ON THE CONTACT AREA.

3.ELECTRICAL:

- 1>.Non-switch Rating:100mA at 50V DC.
- 2>.Switching Rating: 25mA at 24V DC.
- 3>.Contact Resistance: Initial 50mΩ Max.
Contact Resistance: After life 100mΩ Max.
- 4>.Insulation Resistance:100MΩ Min at 500VDC.
- 5>.Dielectric Strength: 500V AC for 60seconds.
- 6>.Switch Capacitance: 5PF Max at 1MHZ.

4.PACKING: 2000pcs/Reel/Box.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE LINER ANGLES >0 ±0.05 >0° ±0.5° >1 ±0.10 >5° ±1.0° >10 ±0.30	PART NAME 品名 1.27mm DIP SWITCH SMT TYPE 8P SHORT KEY W/TAPE SEALED GOLD 3U" TAPE & REEL PACKING ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2022/02/16	PAGE 張數 1 OF 1	REV. 版次 B	PART NO. 料號 C8307-08SYJRB0R