



Specification:  
 Contact Resistance: 30m Ohm Max.  
 Insulation Resistance: 1000M Ohm Min. At 500VDC.  
 Rated Voltage And Current: 1.5A At 250VAC Minimum.  
 Dielectric Withstanding Voltage:  
 750V AC (rms) for 1 Minute(Rev. 1.1)  
 Durability (Life Test): 1500 Cycles  
 Insertion Force: 35 Newton Maximum.  
 Extraction Force: 10 Newton Minimum.

PCB LAYOUT  
(COMPONENT SIDE)

NO.	NAME	MATERIAL	FINISH	REMARK	Q'TY
1	HOUSING	NYLON PA9T G.F.	BLACK		1
2	PIN TERM.	PHOS. BRONZE T:0.25	GOLD/TIN PLATED	Gold1~3u" NI:40~60u" TIN:120u" (100% pure Tin of lead free plating)	4
3	SHELL	BRASS T:0.3	NICKEL PLATED	NI:50u" MINIMUM.	1

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 Betty DATE 制表日 2016/06/23	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 / 1	TOLERANCE 容許公差 X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05 SIZE. 紙張尺寸 A 4 REV. 版次 A	PART NAME 品名 USB B TYPE DIP TYPE 4P FEMALE SMT STRAIGHT TYPE NICKEL SHELL SELECTIVE GOLD PLATING BLACK COLOR ROHS PART NO. 料號 C8317-04BFASB0R