



Specification:
 Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 1000M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1.5A At 250VAC Minimum.
 Dielectric Withstanding Voltage:
 750V AC (rms) for 1 Minute(Rev. 1.1)
 Durability (Life Test): 1500 Cycles
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 10 Newton Minimum.

| NO. | NAME | MATERIAL | FINISH | Q'TY | REMARK |
|-----|--------------|---------------------|-----------------|------|---|
| 1 | HOUSING | PBT G.F. | BLACK | 1 | |
| 2 | PIN TERM. | PHOS. BRONZE:T:0.25 | GOLD-TIN PLATED | 12 | Gold:~3u"; Ni:40~60u"; Ti:120u" (100% pure Tin of lead free plating) |
| 3 | SHELL | BRASS,T:0.3 | NICKEL PLATED | 1 | Ni:80~120u" |
| 4 | SPRING CLIP | BRASS,T:0.3 | NICKEL PLATED | 1 | Ni:80~120u" |
| 5 | REAR SHELL | SPCC,T:0.3 | NICKEL PLATED | 1 | Ni:80~120u" |
| 6 | BOTTOM COVER | PBT G.F. | BLACK | 1 | |

| | | | |
|---------------------|----------------|--|--|
| RoHS Compliant | | 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD. | |
| APPD. 核准 | SCALE 比例 参考 | TOLERANCE X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05 | PART NAME 品名 USB A TYPE DIP TYPE 12P FEMALE 90° HORIZONTAL SELECTIVE GOLD PLATING BLACK COLOR ROHS |
| DWG. 製圖 Betty | UNIT 單位 M M | SIZE. 紙張尺寸 A 4 | PART NO. 料號 C8317-12DFHSB0R |
| DATE 制表日 2024/01/30 | PAGE 張數 1 OF 1 | REV. 版次 B | |