



- 1. Material:**
 Contact: Phosphor Bronze
 Insulator: PBT+30% G.F. UL 94V-0
 Shell: SPCC
- 2. Mechanical:**
 Mating: 35N max.
 Withdrawal Force: 10N min.
 Durability: 1500 cycles min.
- 3. Electrical:**
 Current-max (amps) 1.5A
 Voltage-max (volts) 30V
 Withstanding Voltage 750V AC
 Contact Resistance (ohms) 30 milliohms max
 Insulation Resistance (ohms) 1000 Megohms min.
- 4. Plating:**
 Contacts: Gold And Tin Over Nickel Plated
 Shell: Nickel over all plating.
- 5. Environmental:**
 Temperature Range: -55 to +85

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE x ±0.1 x.x ±0.05 x.xx ±0.005 x.xxx ±0.002	PART NAME 品名 USB A TYPE 4P FEMALE ROHS
DWG. 製圖 ABBY		UNIT 單位 MM	SIZE. 紙張尺寸 A4
DATE 制表日 2015/10/30	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 C8319-04AFSXX0R