



NOTE:

- 1. Material: contacts: C2680 EH T=0.20
- insulator: PBT 94V0
- shell: SPCC T=0.3

NOTE:

- 1. MATERIAL:
 - a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
 - b. CONTACT: BRASS T=0.25mm
(SURFACE PLATING: Au*u" + Sn100u" + Ni50u")
SEE ORDERING INFORMATION
 - c. CRUST: T=0.25mm
(SURFACE PLATING: Ni80u" ~ 100u")
SEE ORDERING INFORMATION
- 2. ELECTRIC:
 - a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 - b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 - c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
 - d. OPERATING TEMPERATURE: -55° C ~ +85° C

RoHS
Compliant

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖		SCALE 比例	
DATE 制表日	UNIT 單位	SIZE 紙張尺寸	PART NO. 料號
2015/4/1	M M	A 4	
	PAGE 張數	REV. 版本	
	1 OF 1	B	USB B TPYE 4P MALE SOLDER TYPE ROHS
			C8319-04BMSXX0R