



Specifications:

1. Electrical:
 - 1.1 Contact Resistance: 30milliohms Max.
 - 1.2 Dielectric Withstanding Voltage: 500V AC Sea Level
 - 1.3 Insulation Resistance: 100MEGA ohms MIN.
2. Material:
 - 2.1 Housing: High Temperature Thermoplastics,LCP
 - 2.2 Contact: Copper Alloy
 - 2.3 Shell:Copper Alloy
- 3.Finish:
 - 3.1 Contact: Gold Plated In Mating Area;
Tin Plated On Solder Tails.
 - 3.2 Shell: Nickel Plated

Recommended PCB Layout

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY		TOLERANCE .X±0.15 .X±.5' .XX±0.05 .X±2' .XXX±0.02 .XX±1"	PART NAME 品名 MINI USB 5P FEMALE B TYPE P.C.B. RIGHT ANGLE TYPE SELECTIVE GOLD PLATING BLACK INSULATOR ROHS
DWG. 製圖 ABBY	SCALE 比例 參考	UNIT 單位 MM	PART NO. C8320-05BFRSB0R 料號
DATE 制表日 2023/03/24	PAGE 張數 1 OF 1	REV. 版次 C	