



SCHEMATIC

P.C.B LAYOUT

□S	L=
2.4X2.4mm	3.6

RATING: DC12V 50mA
 WITHSTAND VOLTAGE: AC250V(50Hz)/min
 CONTACT RESISTANCE: $\leq 30m\Omega$
 INSULATION RESISTANCE: $\geq 100M\Omega$
 TRAVEL TOCLOSURE: $0.25\pm 0.1mm$
 OPERATION FORCE: $160gf\pm 50gf$
 LIFE TEST: 100,000 cycles

6				
5	CONTACT	PBS	1	
4	COVER	SUS	1	Ni-PLATED
3	HOUSING	PA66	1	BLACK
2	TERMINAL	BRASS	4	Ag-PLATED
1	KNOB	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATED

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty		TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 TACT SWITCH SMT TYPE PORD. SIZE: 6X6mm KNOB: SQUARE TYPE KONB HEIGHT : 7.3mm PITCH: 8.5mm OPERATING FORCE: 160g BLACK COLOR ROHS
DWG. 製圖 Betty	SCALE 比例 參考	SIZE. 紙張尺寸 A 4	PART NO. 料號 C8705-FDBBX000R
DATE 制表日 2014/01/14	UNIT 單位 M M PAGE 張數 1 OF 1	REV. 版次 A	