



RATING: DC12V 50mA  
 WITHSTAND VOLTAGE: AC250V(50Hz)/min  
 CONTACT RESISTANCE:  $\leq 30m\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 TRAVEL TO CLOSURE: 0.15mm  
 OPERATION FORCE: 180gf $\pm$ 50gf  
 LIFE TEST: 100,000 cycles

6				
5	TERMINAL	BRASS	4	Ag-PLATED
4	CONTACT	SUS	1	Ag-PLATED
3	KNOB	PA66	1	
2	COVER	SUS	1	
1	HOUSING	PA66	1	BLACK
NO.	DESCRIPTION	MATERIAL	QTY.	PLATED

RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 3.4mm X 3.4mm Tact Switch S.M.T Type H=1.5mm Operating Force: 180gf Button Color: White Color ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO. 料號 C8710-AEWX0000R
DATE 製表日 2015/11/16	PAGE 張數 1 OF 1	REV. 版次 A	