



SPECIFICATION

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	250V AC/1 minute
Operating Force	70±50gf/100±50gf/160±50gf 260±50gf
Travel	0.25mm
Operating Life	200,000 cycles for 260gf 1,000,000 cycles for 160/100gf
Operating Temp.	-40°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

ITEM	DESC.	Q'TY	MATERIALS	TREATMENT	REMARK
1.	METAL STEM	1	SPCF	NI PLATING	-
2.	COVER	1	□ = NICKEL SILVER S = STAINLESS STEEL	□ = NONE S = WITH SILVER PLATING	-
3.	ADHESIVE TAPE	1	TEFLON	NONE	-
4.	TERMINAL	1	PHOSPHOR BRONZE	WITH SILVER PLATING	-
5.	CONTACT	1	STAINLESS STEEL	WITH SILVER CLADDING	-
6.	BASE	1	HIGH - TEMP THERMOPLASTIC LCP	MOLDED BLACK	-

APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名
		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	
DWG. 製圖	Betty	UNIT 單位	PART NO.
DATE 制表日		M M	
2016/07/12		PAGE 張數	料號
		1 OF 1	

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.