



NO (序号)	PART NAME (部件名)	QTY (数量)	MATERIAL (材料)	REMARK (备注)
5	COVER (盖板)	1	SUS304	—
4	STEM (按钮)	1	LCP	WHITE
3	CONTACT FORM (弹片)	1	SUS301	Ag plating
2	HOUSING (基座)	1	LCP	WHITE
1	TERMINAL (端子)	1	PHOSPHOR BRONZE	Ag plating

SPECIFICATION

1. Rating: DC 12V 50mA Max
2. Contact resistance: $100\text{m}\Omega$ MAX
3. Insulation resistance: $100\text{M}\Omega$ Min
4. Dielectric strength: 250VAC/min
5. Operating force: $250\text{gf} \pm 50\text{gf}$
6. Operating life: 100,000 cycles

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		UNSPECIFIED TOLERANCE 未指定的公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	3.2X4.2mm TACT SWITCH BEND OUTWARD TYPE
DATE 制表日	2019/10/07	UNIT 單位 M M	KNOB HEIGHT: 2.5mm OPERATING FORCE: 250gf
		PAGE 張數 1 OF 1	BUTTON COLOR: WHITE COLOR
		REV. 版次 A	REEL PACKING ROHS
			PART NO. 料號 C8735-RCWR0000R