



NOTE:
 1.ALL DIMENSIONS ARE IN MILLIMETERS.
 BRACKETED DIMENSIONS ARE IN INCHES.
 2.GENERAL TOLERANCES $\pm 0.25\text{mm}$
 3.MECHANICAL:
 Operating Force(OF): $160\pm 50\text{gf}$
 Life: $160\text{g}\pm 50\text{g}$, 300,000 CYCLES
 4.ELECTRIAL:
 Switch Rating: 50 mA, 12V DC
 Contact Resistance: 100 m Ω Max
 Insulation Resistance: 500V DC, 100 M Ω Min
 LED Operating Current: 20mA Max.

ITEM	DESC.	Q'TY	MATERIALS	TREATMENT	REMARK
1.	CAP	1	HIGH TEMP THERMOPLASTIC PC	TRANSLUCENT MILKY	-
2.	CAP BASE	1	HIGH TEMP THERMOPLASTIC PA66	BLACK	-
3.	STEM	1	HIGH TEMP THERMOPLASTIC PA66	WHITE	-
4.	CONTACT	1	STAINLESS STEEL SUS301	WITH SILVER CLADDING	-
5.	BASE	1	HIGH TEMP THERMOPLASTIC PA66	BLACK	-
6.	TERMINAL	1	BRASS	WITH SILVER PLATING	-
7.	LED	1	-	-	-

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APFD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 \pm 0.30 .00 \pm 0.20 ANG. \pm 3°	PART NAME 品名 Illuminated Switch With Cap Through Hole Type Operating Force:160gf Cap Color:Silver ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. C8902-BVX00000R
DATE 制表日 2014/02/25	PAGE 張數 1 OF 1	REV. 版次 A	料號