



****RJ45 Plug put In assembly**

Note:
 Waterproof rate: IP68
 UV Resist

9	RJ45 PLUG	Shielded Jack 8Pin
8	ROPE	EPDM Black
7	SEALING NUT	Nylon+GF Black -40~+105°C
6	WIRE CLIP	PA66-V2
5	GASKET	EPDM Black
4	HOUSING	Nylon+GF Black -40~+105°C
3	O-RING	EPDM Black
2	CONNECTOR	Nylon+GF Black -40~+105°C
1	DUST COVER	EPDM Black
NO	PART NAME	INFORMATION

Specification:
 Current Rating : 1.5A
 Voltage Rating :125VAC
 Operating Temp:-20°C ~ +85°C
 Insulation Resistance:1000MΩ
 Dielectric Withstanding Voltage:1KV
 Contact Resistance:40mΩ

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准		TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	Betty	SCALE 比例 參考	WATERPROOF TYPE IP68 TYPE
DATE 制表日	2020/01/20	UNIT 單位 M M	MODULAR PLUG 8P8C W/ SHIELDED
		PAGE 張數 1 OF 1	ASSEMBLY TYPE WITHOUT POWER PIN
			WITH DUST COVER BLACK COLOR ROHS
			PART NO.
			料號 C9402-88XNB000R