


Note:  
Waterproof rate: IP68  
UV Resist

For Panel Thickness Max 5.0mm		
NO	PART NAME	INFORMATION
8	ROPE	EPDM Black
7	DUST COVER	EPDM Black
6	NUT	Nylon+GF Black -40~+105°C
5	GASKET	EPDM Black
4	EPOXY	Black
3	PCB	FR-4
2	RJ45 JACK	Shielded Jack 8Pin or 10Pin
1	HOUSING	Nylon+GF Black-40~+105°C

PIN DEFINITION		
RJ45 8P&10P		RJ45 8P&10P
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
10	_____	10
Shield	_____	Shield

Specification:  
Current Rating : 1.5A  
Voltage Rating : 125VAC  
Operating Temp: -20°C ~ +85°C  
Insulation Resistance: 1000MΩ  
Dielectric Withstanding Voltage: 1KV  
Contact Resistance: 40mΩ



RoHS Compliant		<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 WATERPROOF TYPE IP68 TYPE MODULAR JACK 10PXC GOLD 6U" PLATING TO MODULAR JACK 10PXC GOLD 6U" PLATING INNER TYPE WITH DUST COVER BLACK COLOR
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 C9401-0XKIB000R
DATE 制表日 2020/01/20	PAGE 張數 1 OF 1	REV. 版次 A	