



SPECIFICATIONS

Current Rating: 3Amps
 Insulator resistance: 5000 Megohms min.
 Dielectric Withstanding: AC 500V
 Operating Temperature: -40°C to +105°C
 Insulator Material: PA6T
 Contact Material: Brass
 Plating: Gold flash
 UNIT: MM

UNSPECIFIED TOLERANCE ±0.20

Dimensions list

Contacts Per row	Dimensions	
	A	B
14	21.34	12
16	23.34	14
20	27.34	18
24	31.34	22
26	33.34	24
30	39.34	28
34	43.34	32
40	47.34	38
44	51.34	42
50	57.34	48
68	75.34	66

APPD. 核准 DWG. 製圖 DATE 制表日 2014/1/15	RoHS Compliant <i>Helen</i>	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	TOLERANCE 容許公差 0 ± 0.2 .00 ± ANG ±	PART NAME 品名 BOX HEADER 2.0mm X 2.0mm XXP SMT TYPE GOLD FLASH PLATING PAD+(TUBE OR REEL) PACKING BLACK COLOR ROHS
			SCALE 比例 UNIT 單位 PAGE 張數 1 OF 1	SIZE 紙張尺寸 A4 REV. 版本 A PART NO. 料號 C9510-XXDNGB(P,Q)0R