



NOTE:  
 TEMPERATURE RANGE: -30°C~+70°C  
 RATING: DC30V 0.5A  
 CONTACT RESISTANCE:  $\leq 0.03\Omega$   
 INSULATION RESISTANCE:  $\geq 100M\Omega$   
 WITHSTAND VOLTAGE: AC500V(50Hz) / min  
 WITHDRAW FORCE: 3~20N  
 LIFE TEST: 5,000 cycles

NO.	DESCRIPTION	MATERIAL	Q'TY	REMARKS
5	5# Terminal	Manganese steel strip	1	D.sn
4	1# Terminal	Qsn6.5-0.1 Bronze	1	D.sn
3	2# Terminal	Manganese steel strip	1	D.sn
2	Base	PA66	1	Black Color
1	Bushings	H59 Brass $\phi=6mm$ H=1.2mm	1	Nickel Plating

APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	PART NAME 品名 3.5Φ EARPHONE JACK 3P HEAD TYPE THIRD METAL W/O THREAD TIN PLATING BLACK INSULATOR ROHS
		.0 ± 0.30 .00 ± 0.20 ANG. ± 3°	
DWG. 製圖	Betty	UNIT 單位	PART NO. 料號
DATE 制表日 2023/06/15	PAGE 張數	M M 1 OF 1	

RoHS Compliant **HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**