



**MATERIAL:**

- 1. Flexible Flat Cable UL20706  
60V 105°C Pitch:2.54mm 13 pin L:55mm.
- 2. Terminal: Pitch:2.54 FFC Terminal Tin Plated

ITEM	P	NC	TL	IL	TW	TP	M	S1	S2	S3	S4	A	Tt	T
SIZE	2.54	13	55	-	35.56	30.48	2.54	-	-	-	-	0	0.2	-
TOL±	± 0.2		±2.0	± 3.0	± 0.3	± 0.3	± 0.2	± 0.5	± 0.5	± 1.0	± 1.0	0.5MAX	± 0.02	± 0.05

UL Style	UL20706 60V 105°C	
Conductor	Tin Plated Copper Flat Conductor	
	SIZE	TOL
THICKNESS	0.08	± 0.01
WIDTH	1.45	± 0.03
INSULATION	POLYESTER COLOR:WHITE	
THICKNESS	0.06	± 0.003
STIFFENER	POLYESTER COLOR:BLUE	
THICKNESS	-	± 0.003

<b>RoHS Compliant</b>	<b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>		
	APPD. 核准 BETTY DWG. 製圖 KAREN DATE 制表日 2013/12/04	 SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± .00 ± ANG. ± SIZE 紙張尺寸 A4 REV. 版本 B
	<b>PART NAME 品名</b> 2.54mm FLEXIBLE FLAT CABLE UL20706 105°C 60V 13P BOTH W/MALE TERMINAL CABLE LENGTH=61mm (INCLUDE TERMINAL) ROHS		
	<b>PART NO.</b> 料號 F0806-13P0EE01R		