



UL File No. : E162690
 UL Style : 2651
 Operating Temperature : -20°C to +105°C
 Flammability Rating : UL-VW-1
 Voltage Rating : 300V
 Contact Current Rating:1A

Physical

Insulation Material : Polyvinyl Chloride (PVC)
 Conductor : #28AWG (7*0.127) Stranded Tinned Copper
 #26AWG (7*0.16) Stranded Tinned Copper
 Color : Grey With Red Edge

Electrical

Impedance : 115Ω (Unbalanced)
 Capacitance : 12.2 pF/ft.
 Inductance: 14μH/ft
 Propagation Delay : 1.4 ns/ft.
 Insulation Resistance : 1GΩ/M min.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Helen	 SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 FLAT CABLE 1.27mm UL2651 26AWG STRANDED GREY COLOR XXP W/RED SIDE 1 ROLL=100FEET ROHS LOW-LEAD
DWG. 製圖 Yumi		SIZE. 紙張尺寸 A 4	PART NO. 料號 F0813-XXPAF000R
DATE 制表日 2010/10/07		REV. 版次 B	