



- Specifications
- Voltage Rating: 50V AC/ DC
 - Current Rating: 2A AC/DC
 - Withstanding Voltage: 500V AC/Minute
 - Insulation Resistance: 100MΩ Min.
 - Temperature Range: -25°C~+85°C
 - Contact Resistance: 20mΩ Max.
 - After enviornmetntal testing: 20mΩ Max.

- Material:
- Housing: Nylon66 UL94V-0, Halogen-Free
 - Color: Black or White

Poles	Dimensions (mm)	
	A	B
2	1.20	2.60
3	2.40	3.80
4	3.60	5.00
5	4.80	6.20
6	6.00	7.40

RoHS Compliant		 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	GENERAL TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1	PART NAME 品名 1.2mm HOUSING 1XXXP NYLON66 UL94-V0 ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE. 紙張尺寸 A4	PART NO. 料號 H1201-XXPX1000R
DATE 制表日 2017/08/11	PAGE 張數 1 OF 1	REV. 版次 A	