



**SPECIFICATIONS**  
 Current Rating: 1A AC,DC  
 Voltage Rating: 150V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0

Circuit No.	Dimensions			
	A	B	C	D
2X05P	5.00	10.40	8.00	9.00
2X06P	6.25	11.65	9.25	10.25
2X07P	7.50	12.90	10.50	11.50
2X10P	11.25	16.65	14.25	15.25
2X15P	17.50	22.90	20.50	21.50
2X17P	20.00	25.40	23.00	24.00
2X18P	21.25	26.65	24.25	25.25
2X20P	23.75	29.15	26.75	27.75
2X21P	25.00	30.40	28.00	29.00
2X25P	30.00	35.40	33.00	34.00

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 制表日 2016/8/8	<i>Helen</i>	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3° SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	PART NAME 品名 1.25mm HOUSING 2XXXXP KAKHI COLOR ROHS PART NO. 料號 H1250-XXPD6000R